




MAXUS
ELECTRIC VEHICLES



/// // // // //

MAXUS eDeliver 5

Designed for the Future of Delivery



VIEW WEBSITE







GREEN EFFICIENCY, MAXIMUM PERFORMANCE

The eDeliver 5 is an advanced electric Light Commercial Vehicle (LCV) designed for optimised delivery operations, offering robust performance and extensive cargo space.

Leading the way in green technology, the eDeliver 5 ensures absolute efficiency without compromising capability or reliability. It boasts an impressive range on a 64kWh battery, with superior payload and towing performance.

Key safety features include lane keep assist, departure warning, automatic emergency braking, forward collision warning, and intelligent high beam control for nighttime driving.

Remote access and a user-friendly dashboard allow for vehicle locking/unlocking, route planning, range visualisation, and scheduled charging, ensuring a seamless workflow and minimal downtime.

BUILT FOR URBAN DELIVERY




1930kg
MAXIMUM
CVW



1200kg
MAXIMUM
PAYLOAD



750kg
TOWING
CAPACITY
(BRAKED TRAILER)



120km/h
MAXIMUM
SPEED

WLTP CITY RANGE 436 km
WLTP COMBINED RANGE 301 km



ELECTRIFYING PERFORMANCE

Motor Specs

Rated/Peak Power	120kW
Rated/Peak Torque	240 N.m
0-50km/h	5.1 (sec)
0-100km/h	10.9 (sec)

Charge Time

20% - 80% DC	36min/70kW (S)
20% - 80% AC	4h/11kW (S)

Battery Specs

Battery Capacity	64kWh
Energy Consumption	23.9kWh/100km
Battery	Lithium iron phosphate



STANDARD EQUIPMENT



Comfort and Convenience:

- Manual air conditioning
- Heated front seats
- Power front windows (one click up & down)
- 12.3" touch screen with MP5, USB, Bluetooth, Wireless Carplay & Android Auto & DAB
- Keyless start (PEPS system)
- LED headlights
- Power heated exterior mirrors




Safety:

- Tyre pressure monitoring system
- ABS: Anti-lock Braking System
- EBD: Electronic Brakeforce Distribution
- ESC: Electronic Stability Control
- Front and Side Airbags for driver & front passengers
- Safety belt reminder
- 360 around-view system
- Rear parking sensor



**VISIT OUR
WEBSITE**

<https://maxus.co.za>



VIEW WEBSITE

STANDARD EQUIPMENT

continued



Suspension:

- Front McPherson Independent Suspension
- Rear Leaf Spring Suspension



Braking:

- Electronic parking brake
- Front and Rear Disc Brakes
- Braking Energy Recovery: 3 levels adjustable



*Standard specifications may vary from the list above, depending on the vehicle model.

*Estimated range & energy consumption under EU WLTC test standard. Actual range & energy consumption varies with conditions such as temperature, operation of air conditioner, driving mode, route conditions, battery capacity loss and loading mass.

Images shown in this brochure are for illustration purposes only. Actual vehicles may differ and are subject to change. Specifications, standard equipment, options, fabrics and colours are subject to change without notice. Some features may be unavailable when your vehicle is built. Some vehicles are pictured with options that may be available at extra cost or may not be available on certain models. Ask about availability of options and verify that the vehicle you ordered includes the equipment you ordered.

VISIT OUR WEBSITE

<https://maxus.co.za>




VIEW WEBSITE

DETAILED SPECIFICATIONS

	MAXUS eDELIVER 5	
WEIGHTS & PAYLOAD	GVW (kg)	3150(2S)/3195(3S)
	CVW (kg)	1930
	Payload GVW-CVW(kg)	1220(2S)/1265(3S)
	GVW axle load: front/rear(kg)	1297(2S)/1853(2S) 1343(3S)/1852(3S)
	Max axle load: front/rear(kg)	1450/1800
	GTM (kg)	4650(2S)/4695(3S)
	Towing capacity (Braked/Unbraked)(kg)	1500/750
POWER, DRIVING & STEERING	Driving wheel	FWD
	EPS(Electric Power Steering)	S
	Max speed (km/h)	120
	Min turning diameter (m)	12.8
	Approach angle/departure angle (CVW)(°)	24.8/19.6
	Approach angle/departure angle (GVW)(°)	21.1/16.8
	Tyre & Spare Tyre	195/65 R16C

VISIT OUR WEBSITE

<https://maxus.co.za>



VIEW WEBSITE

DIMENSIONS & CAPACITIES	Sliding door	Double
	Overall length (mm)	5250
	Overall width (mm)	1874
	Overall height (mm)	2180
	Loadspace width (mm)	1704
	Loadspace height (mm)	1675
	Max loadspace width between wheel arches (mm)	1250
	Slide door width (mm)	873
	Slide door height (mm)	1243
	Ground clearance of the front axle (mm)	148
	Ground clearance of the rear axle (mm)	142
	Battery thermal management: liquid cooling & liquid heating	S
	Ground clearance between axles (mm)	145
BATTERY & CHARGING	AC Charging Cable	S
	11kW AC charging	S
RANGE	Autonomy WLTP Combined (km)	300
	Autonomy WLTP Urban (km)	380

**VISIT OUR
WEBSITE**

<https://maxus.co.za>



VIEW WEBSITE